

CROSS REFERENCE CHART

TC	Passive Plus	AVX / ATC		Standard Voltage (VDC)	Extended Voltage	Case Size (inches)	Value Range	
P 9 0	0505P	SQCAxM	100A	150	300	.055 x .055	.1pF-100pF	
	0708N	N/A	180R	500	N/A	.070 x .080	1pF-100pF	
	1111P	SQCBxM	100B	500	1500	.110 x .110	.1pF-1000pF	
	2225P	HQCCxM	100C	2500	3600	.220 x .250	.5pF-2700pF	
	3838P	HQCExM	100E	3600	7200	.380 x .380	.5pF-5100pF	
N P 0	0505C	SQCAxA	700A	150	300	.055 x .055	.1pF-1000pF	
	1111C	SQCBxA	700B	500	1500	.110 x .110	.1pF-10,000pF	
	2225C	HQCCxA	700C	2500	3600	.220 x .250	.5pF-2700pF	
	3838C	HQCExA	700E	3600	7200	.380 x .380	.5pF-5100pF	
	6040C	N/A	N/A	5000	8000	.600 x .400	1pF-6800pF	
	7676C	N/A	N/A	5000	8000	.760 x .760	1pF-20,000pF	
	1313C	N/A	N/A	10000	N/A	1.30 X 1.30	200-120000pF	
N P 0	0201N	N/A	NA	25	50	.020 x .010	.1pF-100pF	
	0402N	UQCL	600L	200	250	.040 x .020	.1pF-33pF	
	0603N	UQCS	600S	250	N/A	.060 x .030	.1pF-100pF	
	0805N	UQCF	600F	250	N/A	.080 x .050	.1pF - 220pF	
N P 0	*0603N	UQ CA	800A	250	N/A	.060 x .030	.1pF-100pF	
	0708N	SQCB	800R	500	N/A	.065 x .080	1pF - 100pF	
	1111N	UQ CB	800B	500	1000	.110 x .110	.2pF-1000pF	
	2225C	HQCCxA	800C	2500	3600	.220 x .250	.5pF-2700pF	
	3838C	HQCExA	800E	3600	7200	.380 x .380	.5pF-5100pF	
X 7 R	0505X	SQCAxC	200A	50	N/A	.055 x .055	470pF-.01uF	
	1111X	SQCBxC	200B	50	N/A	.110 x .110	4700pF-.1uF	
	2225X	N/A	900C	300	N/A	.220 x .250	.01uF-1uF	
*Similar electrical but different case size								
B R O A D B A N D S	Passive Plus	AVX / ATC		Fo	IL	WVDC	Size (inches)	Value
	01005BB 01005BB104MW4R0	N/A	N/A	16kHz>67GHz	<1dB	4V	.010 x .005	100,000pF (100nF)
	01005BB 01005BB103MW100	N/A	N/A	COMING SOON				
	0201BB** 0201BB104KW160	N/A	530Z /10V	16kHz>40GHz	<1dB	16V	.020 x .010	100,000pF (100nF)
	0201BB** 0201BB103KW250	GX01	550Z /10V	160kHz>32GHz	<1dB	25V	.020 X .010	10,000pF (10nF)
	0402BB 0402BB104KW160	N/A	530L /16V	16kHz>18GHz	<1dB	16V	.040 x .020	100,000pF (100nF)
	0402BB** 0402BB104KW500	GX02	550L /16V	16kHz>50GHz	<1.2dB	50V	.040 x .020	100,000pF (100nF)
	0402BB 0402BB103KW160	N/A	520L /16V	160kHz>16.5GHz	<1dB	16V	.040 x .020	10,000pF (10nF)
	0402BB 0402BB103KW500	N/A	N/A	160kHz>40GHz	<1dB	50V	.040 x .020	10,000pF (10nF)
	0603BB**	GX03	550S	COMING SOON				
	0805BB 0805BB103KW101	N/A	N/A	160kHz>3GHz	<.25dB	100V	.080 x .050	10,000 (10nF)

** Available in both RoHS and Gold Termination;

See catalog and website for complete capacitance, tolerance & WVDC availability.